
# **Current Meter**



Add a rugged, single-point current meter to your Spotter Platform to measure subsurface current speed and direction in real time.

Sample precisely, rapidly, and at depth with motion-tolerant, tilt-compensated performance and energy-efficient solar-rechargeable power.

**FEATURED IN** 


# **Spotter Currents**

A turnkey solution for real-time subsurface current monitoring.

## **HIGH IMPACT USE CASES**

- Offshore Site Assessment
- Maritime Navigation Safety
- Ocean Circulation Studies

<u>Learn More →</u>



Sensor         Aanderaa 4830 ZPulse® Doppler Current Sensor (DCS)           Category         Single-point acoustic Doppler current meter           Current Speed         Accuracy: ±0.15 cm/s or 1% reading Resolution: 0.1 mm/s Range: 0–300 cm/s (0–100 cm/s max when deployed)           Current Direction         Accuracy: ±5° (for tilt 0–15°) ±7.5° (tilt 15–35°) Resolution: 0.01° Range: 0–360° (magnetic)           Tilt Circuitry         Accuracy: ±1.5° Resolution: 0.01° Range: 0–35°           Compass Circuitry         Accuracy: ±3° Resolution: 0.01° Frequency: 1.9 to 2.0MHz           Temperature         Accuracy: ±0.1°C Resolution: 0.01°C Range: -5°C – 40°C           Sampling Method         ~150 pings/axis; vector average; user-set interval           Transducers         4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m           Maximum Depth         50 m           Power Supply         Spotter's Li-ion battery (solar-rechargeable)           Size (Dia. x Len.)         120 mm × 108 mm           Weight         1.8 kg (~4 lbs)           Interface Standard         Bristlemouth-native (plug-and-play)	Core Specifications	
Current Speed  Accuracy: ±0.15 cm/s or 1% reading  Resolution: 0.1 mm/s  Range: 0–300 cm/s (0–100 cm/s max when deployed)  Current Direction  Accuracy: ±5° (for tilt 0–15°) ±7.5° (tilt 15–35°)  Resolution: 0.01°  Range: 0–360° (magnetic)  Tilt Circuitry  Accuracy: ±1.5°  Resolution: 0.01°  Range: 0–35°  Compass Circuitry  Accuracy: ±3°  Resolution: 0.01°  Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C - 40°C  Sampling Method  -150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  120 mm × 108 mm  Weight  1.8 kg (~4 lbs)	Sensor	
Resolution: 0.1 mm/s  Range: 0–300 cm/s (0–100 cm/s max when deployed)  Current Direction  Accuracy: ±5° (for tilt 0–15°) ±7.5° (tilt 15–35°)  Resolution: 0.01°  Range: 0–360° (magnetic)  Tilt Circuitry  Accuracy: ±1.5°  Resolution: 0.01°  Range: 0–35°  Compass Circuitry  Accuracy: ±3°  Resolution: 0.01°  Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C – 40°C  Sampling Method  -150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  120 mm × 108 mm  Weight  1.8 kg (~4 lbs)	Category	Single-point acoustic Doppler current meter
Range: 0–300 cm/s (0–100 cm/s max when deployed)  Current Direction  Accuracy: ±5° (for tilt 0–15°) ±7.5° (tilt 15–35°)  Resolution: 0.01°  Range: 0–360° (magnetic)  Tilt Circuitry  Accuracy: ±1.5°  Resolution: 0.01°  Range: 0–35°  Compass Circuitry  Accuracy: ±3°  Resolution: 0.01°  Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C – 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  120 mm × 108 mm  Weight  1.8 kg (~4 lbs)	Current Speed	Accuracy: ±0.15 cm/s or 1% reading
Current Direction  Accuracy: ±5° (for tilt 0–15°) ±7.5° (tilt 15–35°)  Resolution: 0.01°  Range: 0–360° (magnetic)  Tilt Circuitry  Accuracy: ±1.5°  Resolution: 0.01°  Range: 0–35°  Compass Circuitry  Accuracy: ±3°  Resolution: 0.01°  Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C – 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  1.8 kg (~4 lbs)		Resolution: 0.1 mm/s
#7.5° (tilf 15–35°)  Resolution: 0.01°  Range: 0–360° (magnetic)  Tilt Circuitry  Accuracy: ±1.5°  Resolution: 0.01°  Range: 0–35°  Compass Circuitry  Accuracy: ±3°  Resolution: 0.01°  Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C – 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  1.8 kg (~4 lbs)		
Range: 0–360° (magnetic)  Tilt Circuitry  Accuracy: ±1.5°  Resolution: 0.01°  Range: 0–35°  Compass Circuitry  Accuracy: ±3°  Resolution: 0.01°  Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C – 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  120 mm × 108 mm  Weight  1.8 kg (~4 lbs)	Current Direction	<b>3</b>
Tilt Circuitry  Accuracy: ±1.5°  Resolution: 0.01°  Range: 0–35°  Compass Circuitry  Accuracy: ±3°  Resolution: 0.01°  Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C – 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  1.8 kg (~4 lbs)		Resolution: 0.01°
Resolution: 0.01°  Range: 0–35°  Compass Circuitry  Accuracy: ±3°  Resolution: 0.01°  Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C – 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  1.8 kg (~4 lbs)		Range: 0–360° (magnetic)
Range: 0–35°  Compass Circuitry  Accuracy: ±3°  Resolution: 0.01°  Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C – 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  120 mm × 108 mm  Weight  1.8 kg (~4 lbs)	Tilt Circuitry	Accuracy: ±1.5°
Compass Circuitry  Accuracy: ±3°  Resolution: 0.01°  Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C - 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  120 mm × 108 mm  Weight  1.8 kg (~4 lbs)		Resolution: 0.01°
Resolution: 0.01° Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C Resolution: 0.01°C Range: -5°C - 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  120 mm × 108 mm  Weight  1.8 kg (~4 lbs)		Range: 0–35°
Frequency: 1.9 to 2.0MHz  Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C - 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  120 mm × 108 mm  Weight  1.8 kg (~4 lbs)	Compass Circuitry	Accuracy: ±3°
Temperature  Accuracy: ±0.1°C  Resolution: 0.01°C  Range: -5°C - 40°C  Sampling Method  ~150 pings/axis; vector average; user-set interval  Transducers  4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth  50 m  Power Supply  Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.)  120 mm × 108 mm  Weight  1.8 kg (~4 lbs)		Resolution: 0.01°
Resolution: 0.01°C  Range: -5°C – 40°C  Sampling Method ~150 pings/axis; vector average; user-set interval  Transducers 4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth 50 m  Power Supply Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.) 120 mm × 108 mm  Weight 1.8 kg (~4 lbs)		Frequency: 1.9 to 2.0MHz
Range: -5°C – 40°C  Sampling Method ~150 pings/axis; vector average; user-set interval  Transducers 4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth 50 m  Power Supply Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.) 120 mm × 108 mm  Weight 1.8 kg (~4 lbs)	Temperature	Accuracy: ±0.1°C
Sampling Method ~150 pings/axis; vector average; user-set interval  Transducers 4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth 50 m  Power Supply Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.) 120 mm × 108 mm  Weight 1.8 kg (~4 lbs)		Resolution: 0.01°C
Transducers 4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m  Maximum Depth 50 m  Power Supply Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.) 120 mm × 108 mm  Weight 1.8 kg (~4 lbs)		Range: -5°C – 40°C
Maximum Depth50 mPower SupplySpotter's Li-ion battery (solar-rechargeable)Size (Dia. x Len.)120 mm × 108 mmWeight1.8 kg (~4 lbs)	Sampling Method	. •
Power Supply Spotter's Li-ion battery (solar-rechargeable)  Size (Dia. x Len.) 120 mm × 108 mm  Weight 1.8 kg (~4 lbs)	Transducers	4 units; 1.9–2.0 MHz; 2° beam; cell: 0.4–1.0 m
Size (Dia. x Len.) 120 mm × 108 mm  Weight 1.8 kg (~4 lbs)	Maximum Depth	50 m
Weight 1.8 kg (~4 lbs)	Power Supply	Spotter's Li-ion battery (solar-rechargeable)
	Size (Dia. x Len.)	120 mm × 108 mm
Interface Standard Bristlemouth-native (plug-and-play)	Weight	1.8 kg (~4 lbs)
	Interface Standard	Bristlemouth-native (plug-and-play)

# Data Access & Analysis

## **Spotter Dashboard**

View real-time data and insights

#### **API Access**

Retrieve data programmatically with our secure API

## **Onboard Storage**

Download data via SD card for offline analysis

## **Transmission**

Satellite and cellular options

# Deployment & Best Practices

# **Configuration Options**

Ideal for moored coastal deployments (single Spotter or network). Supports up to two current sensors per Smart Mooring, plus one additional device (max 3 total).

## **Max Operational Conditions**

Up to 100cm/s current velocity

#### Calibration

Recalibrate annually (~0.50% FS drift)

## Mounting

Mount with sensor head (pressure port) pointing downward to prevent debris clogging

## **Remote Configuration & Controls**

Direct control via Spotter Dashboard, binary/ASCII commands, and Sofar remote support

## Maintenance

Rinse with fresh water after retrieval. Clean the pressure port to remove debris

